

## 4KCHANGER-TC1 Selector encastrable en mesa

4KCHANGER-TC1 es una caja de conexiones multiformato que provee de conexiones de video, carga y ethernet. Ideal para salas de reuniones. Detecta automáticamente la entrada conectada. También permite selección manual mediante un botón.



## CARACTERÍSTICAS:

- Permite cuatro entradas de video. Type-C, VGA + 3.5mm Audio, Mini DP & HDMI
- Selección de entrada automática o manual mediante botón
- Resolución máxima 4K@60Hz
- Conectores de carga USB-A & USB-C

Specifications		4KCHANGER-TC1
Power		DC 24V / 1.5A
POE		NO
Extension		NO
AV output		HDMI 19Pin Female
Dimensions (L-W-H)		7.2 in (184mm) x 3.1 in (80mm) x 3.6 in (90mm)
Product Weight		аррх. 735 g
Package Box Dim. (L-W-H)		9.8 in (248 mm) x 7.7 in (195 mm) x 3.7 in (95 mm)
Package Weight		аррх. 1268 g
Audio format		Dolby True HD/DTS HD/Dolby Atoms/ Dolby Digital 5.1 / Dolby Digital Plus/ DTS 5.1/LPCM
HDMI Max Frequency		297MHz
HDMI Max Bandwidth		8.91Gbps
AV Input Resolutions	Mini DP	4096 x 2160, 3840 x 2160, 2560 x 1600, 2560 x 1440, 1920 x 1200, 1920 x 1080, 1600 x 1200, 1600 x 900, 1280 x 720, 1024 x 768, 800 x 600
	Type-C	
	HDMI	
	VGA	1920 x 1080, 1600 x 1200, 1600 x 900, 1280 x 720, 1024 x 768, 800 x 600
Charging	USB 2.0 A	Support 5V / 2.0A
	USB 3.1 C	Support 5V / 2.0A
Output HDMI Length to Display		4K/AWG 282m; 4K/AWG 265m
Ethernet Pass-Through		YES
Operation temperature		23°F ~ 104°F (-5°C ~ 40°C)
Storage temperature		5°F ~ 131°F (-15°C ~ 55°C)
Operation humidity range		5 to 85%RH ( No Condensation )
Storage humidity		5 ~95%RH (No Condensation)
Max. Analog Resolutions		1920*1080 60 Hz
Max. Digital Resolutions		3840*2160 60Hz and 4096*2160 60Hz

Unit Number	Description
4KCHANGER-TC1	4KCHANGER Table Connective with input of Type C, VGA+3.5mm Audio, Mini DP & HDMI, auto-detect sources,
4KCHANGER-ICI	switch botton, single HDMI output
4KCHANGER-TC2	4KCHANGER Table Connective with a Extender for distance extention and connection via 30M RJ45 Cat. 6;
ANCHAINGER-ICZ	input: Type C, VGA+3.5mm Audio, Mini DP & HDMI, auto-detect sources, switch button, single HDMI output

Tlfn.: +34 91 653 40 95